

DANUSER®

• EST. 1910 •

EP HEAVY DUTY AUGER SERIES



Lifetime Warranty Covering Output Pull Out

Innovative planetary design with fewer internal components that are completely sealed and running in oil

Forged planetary housing and output with tapered roller bearings

Compact housing design and hoses routed out the top allow you to dig deeper and in tighter locations

Utility-style housing with integrated ears for added strength

3-year warranty on drive unit

DRIVE UNITS

	MODEL EP6			MODEL EP10			MODEL EP15			
PSI →	2000	2500	3000	2000	2500	3000	2000	2500	3000	← PSI
GPM ↓	SPEED			SPEED			SPEED			GPM ↓
	TORQUE (ft.-lbs.)			TORQUE (ft.-lbs.)			TORQUE (ft.-lbs.)			
6	36 RPM									6
	1014	1267	1520							
8	48 RPM									8
	1014	1267	1520							
10	60 RPM			48 RPM						10
	1014	1267	1520	1270	1587	1904				
12	73 RPM			58 RPM						12
	1014	1267	1520	1270	1587	1904				
14	85 RPM			68 RPM						14
	1014	1267	1520	1270	1587	1904				
15	91 RPM			72 RPM			49 RPM			15
	1014	1267	1520	1270	1587	1904	1874	2342	2811	
18				87 RPM			59 RPM			18
				1270	1587	1904	1874	2342	2811	
20				97 RPM			65 RPM			20
				1270	1587	1904	1874	2342	2811	
24							78 RPM			24
							1874	2342	2811	
28							92 RPM			28
							1874	2342	2811	
30							98 RPM			30
							1874	2342	2811	
	Max. Auger Dia.: 24" Hyd. Flow: 6 - 15 GPM Max. Hyd. PSI: 3000 Gearbox Ratio: 3.86:1 Output: 2" Hex No Case Drain Req'd.			Max. Auger Dia.: 30" Hyd. Flow: 10 - 20 GPM Max. Hyd. PSI: 3000 Gearbox Ratio: 3.86:1 Output: 2" Hex No Case Drain Req'd.			Max. Auger Dia.: 36" Hyd. Flow: 15 - 30 GPM Max. Hyd. PSI: 3000 Gearbox Ratio: 3.86:1 Output: 2" Hex No Case Drain Req'd.			

Yellow shaded areas indicate recommended operating ranges.

Output speed and torque specifications are based on theoretical values and are provided for comparative purposes only.



Mounts Available For

Skid-Steers, Tractor Loaders, Mini-Excavators, Backhoes, Excavators, Telescopic Handlers, Articulated Loaders, & Integrated Tool Carriers



Hose kits and couplers available.

EP HEAVY DUTY AUGER SERIES


Danuser performance at an exceptional price!

AUGERS

- Hardened Bolt-On Teeth (FAB and TREE Augers)
- Hardened Drive-In Teeth (CAST Augers) - Standard includes:
 - Gage Teeth in Outside Positions
 - Wisdom Teeth in Inside Positions (FAB and TREE Augers)
 - Chisel Teeth in Inside Positions (CAST Augers)
- Hardened Fishtail Point
- Heavy-Duty Double Flighting
- 2" Hex Collars
- 4' Standard Length
 - 3', 5', and 6' Lengths Priced Upon Request
- Fixed and Variable Auger Extensions Available
- Auger Adapters Available

FAB

Light to Moderate Ground Conditions




Available Diameters

4", 6", 8", 9", 10", 12",
15", 16", 18", 20", 24",
30", 36"

TREE

Tree and Shrub Planting



Available Diameters

18" - 9", 24" - 12",
30" - 15", 36" - 18"

CAST

Difficult Ground - Fracturable Rock, Asphalt, Frozen Ground, Heavy Clay, & Compacted Soils



Available Diameters

6", 8", 9", 10", 12",
15", 16", 18", 20", 24",
30", 36"

BULLET ROCK

Solid Rock, Concrete, Fracturable Rock, Asphalt, Frozen Ground, and Compacted Soils



Available Diameters

4.5", 6", 7", 8", 9", 10", 12",
14", 16", 18", 24", 30", 36"

NOTE: As with all rock augers, performance depends upon down force applied to the auger.

FISHTAIL POINTS



Dirt=D

Hardfaced=HF

Carbide=C

TEETH

GAGE



D

HF

WISDOM



D

HF

C

CHISEL



D

HF

C



EP HEAVY DUTY AUGER SERIES

Visit danuser.com for more Danuser attachments.



Established in 1910, DANUSER has been family owned and operated by four generations. We have manufactured auger systems since 1943. With over 65 years of design and manufacturing experience, our machines have dug millions of holes. Today our commitment to our customer remains to design and build products that are the benchmark of quality, reliability, and longevity. In the words of our founder K.B. Danuser, "Good enough won't do - it must be right."

DANUSER manufactures several attachments for various equipment, serving several industries worldwide. Please visit www.danuser.com to see our full line of attachments.



500 E. 3rd Street
P.O. Box 368
Fulton, MO 65251

573.642.2246 **tel**
573.642.2240 **fax**
sales@danuser.com

danuser.com

Danuser reserves the right to make changes in design, specifications, and prices without notice and without incurring any obligation relating to such changes.

Form No. 3216